



Litre V-twin Engine CFMOTO

The CFORCE 1000 OVERLAND is powered by a 75-horsepower 963cc V-twin engine, bringing the ultimate combination of durability and performance to the trails. The liquid-cooled 8-valve engine features BOSCH EFI for crisp and consistent power throughout the rpm range, ensuring the robust 79 Nm torque has the muscle to take on any size adventure at any elevation.



HDPE skid plates

Protecting the CFORCE 1000 OVERLAND from trail elements are durable full-length skid plates. Made from 8mm thick high-density polyethylene (HDPE), these skid plates, including the front, central, rear and footwell plates, help protect the vehicle and allow you to glide over rocks, stumps and any other obstacles in your path.



CF-connect Cargo system

Head out for your multi-day OVERLAND experience with plenty of room for everything you need. Two remium cargo boxes install easily without any modification and provide 146 liters (105L + 41L) of combined storage space. The 41L center box offers comfort pads for the driver, or can be removed to allow for an ergonomic passenger seat. Weather resistance [IP54] means your belongings stay dry and protected from water and dust

overand

enhance low-light capabilities, and add to the menacing look.

Overland premium paint

The unique premium paint of the CFORCE 1000 OVERLAND is a sight to behold. Inspired by one of the hardest ores in nature (second only to the diamond), the granite finish shimmers with a metallic luster, and is highlighted by the electric-blue trim. The all-new graphics draw inspiration from the OVERLAND mountain peaks, and are color-matched to the beadlock rims.

Heavy duty bumper with LED lights


The aggressive look of the CFORCE 1000 OVERLAND is highlighted by heavy-duty steel bumpers, front and rear. Thick 38mm steel-tube, coated with an anti-corrosion finish, protect the front grill and headlights from whatever the rugged back country might throw its way. A pair of 18w LED flood lamps

Beadlock wheels

Factory-installed 14-inch aluminium wheels with beadlock rims are standard on the CFORCE 1000 OVERLAND. The premium aluminium beadlock rings with 16 bolts provide the ultimate secure fit, allowing you to run low air pressure for a wider contact patch and increased traction. Let the beefy 27-inch tyres gnaw away at rugged terrain while your footing remains secure and the 1000cc engine keeps you moving forward.







Rear Rack Extender Assembly

Code: 9AW#-802400-2000

Features:

- Steel Tube Diameter: 6 22mm
- Easy to install
- E-coated with black powder coat
- Durable and solid
- Helps keep cargo securely in place




Synthetic Winch Rope

Code: 7020-800750

Features:

- High strength winch rope, pull up to 4500 lbs
- Rope length 12 meters
- · Light weight, easy to carry
- Durable, sea water resistance,
 UV resistance and thermal shock resistance
- Convenient, fast and safe operation
- Can be used on any CFMOTO vehicle equipped with a winch



A-arm Protector Assembly

Code: 9AW#-804200-2000

Features:

- Made of high strength aluminum (thickness 5mm)
- Painting Black
- Ultimate durability
- High impact strength



Hitch Kit (136mm)

Code: 7000-808100

Features:

- 2" hitch kit for ATV/UTV
- 136mm length towing bar (from pin shaft hole to hitch ball hole)
- CFMOTO offers two different lengths of hitch receiver to choose from



Hitch Kit (290mm)

Code: 9AW#-808100

Features:

- 2" hitch kit for ATV/UTV
- 136mm length towing bar (from pin shaft hole to hitch ball hole)
- CFMOTO offers two different lengths of hitch receiver to choose from

Vehicle Cover



Winch Rope Fairlead

Code: 7030-150701

Features:

■ Can be used on any CFMOTO vehicle equipped with a winch

OVERALL DIMENSIONS

ENGINE

Length x Width x Height 2310×1264×1420 mm 1480 mm Seat Height 585 mm Minimum Ground Clearance 300 mm Minimum Turning Diameter 7.8 m 490 kg (of CFORCE 1000) Curb Weight Payload Capacity 240 kg (Including driver) 27.6 L Fuel Capacity

V-Twin cylinder, Liquid cooled, 4-stroke,SOHC,8-Valve Engine Type 963 cc CVT

Drive	Switchable 2WD/4WD
Brake	Four-wheel side brake (CBS) + rear wheel side parking
Suspension	Front: Double A-arm, independent suspension
	Rear: Trailing arm, independent suspension
Shock Absorber	Piggy back airshocks,
	adjustable compression,
	Rebound and preload
tires & wheels	27 inch cst off-road tires
	14 inch beadlock wheels
Color(s) Available	Granite Ridge
	VSX Midnight

